



CLIMATE MASTER

27 Series

WATER TO AIR

HEAT PUMPS

VERTICAL MODEL
HORIZONTAL MODEL

Better Cooling... Better Heating... Economically

CHOOSE FROM VERTICAL AND HORIZONTAL MODELS

2 Electrical Options

Different Return Air Configurations

Ease of Installation

Versatility of Application





Compact, Space-Saving Design

Designed & Tested for High Efficiency

Superior Accessibility

Acoustically Improved



ADVANCED FEATURES and SPECIFICATIONS

MAKE CLIMATE MASTER YOUR BEST BUY IN ALL WEATHER COMFORT...

The Climate Master[®] is a complete factory-packaged water-to-air heat pump that provides total comfort. Each unit is designed and built per the specifications listed below:

Cabinet:

The cabinet is made of heavy gauge, galvanized steel, and painted electro-statically to prevent corrosion. The interior of the cabinet is lined with high density, coated insulation with improved thermal insulating and accoustical absorbtion characteristics. The units have access panels for ease of inspection and service to all components. The design incorporates externally stubbed water and drain (FPT) connections in the front of the unit for easy installation. The electrical power, control voltage wiring and control box are also accessible from the front of the unit. The supply air opening is provided with a duct collar and the return air incorporates a filter rack permitting removal of the filter in any direction (also optionally available is a flanged filter rack for ducted returns). The horizontal unit has threaded fasteners on the top for ceiling suspended installation.

Compressor:

The hermetic compressor is internally spring-mounted and mounted in the cabinet on rails with vibration isolators for quiet, smooth running operation. The compressor is furnished with internal (line break) motor protection and features an anti-slug device for extended life.

Reversing Valve:

The reverse cycle feature is provided by a four way electromagnetic reversing valve designed for low pressure drops and reliable operation.

Refrigerant-To-Water Heat Exchanger:

The heat exchanger is coaxial (tube-in-tube) spirally wound with booster fins on the refrigerant side to provide optimum heat transfer. The inner (water) tube is available in copper or 90/10 cupro-nickel construction designed to withstand water pressures of 500 psi. The outer (refrigerant) tube is made of primed and painted steel. Design working pressure on the refrigerant side is 450 psi.

Air-To-Refrigerant Heat Exchanger:

The large face area, fin coil heat exchanger utilizes 5/16" staggered copper tubes with rippled and corrugated aluminum fins for added heat transfer. The refrigerant circuiting is designed for optimum pressure drops and efficiency.

Refrigerant Control:

The optimum factory charge of Refrigerant 22 is metered by precisely designed capillary tubes. The critical charge and sizing of capillary tubes is laboratory researched for balancing on the cooling and heating modes at varied conditions. The refrigerant piping is factory pressure and leak tested. Abnormal pressures within the refrigerant circuit are prevented with safety high and low pressure switches. Charging and service ports are provided on the high and low pressure sides of the unit as standard equipment.

Blower and Motor:

The centrifugal type blower wheel and housing is custom designed for quiet operation and efficient air delivery. The blower is close-coupled to the motor with inherent thermal overload protection. Each unit is provided with a high velocity type disposable filter.

Controls:

The control box, easily accessible from the front panel, includes a 24 volt control transformer, compressor contactor, blower and impedance relays. The single phase model is furnished with a run capacitor. Completely factory wired, the circuit features a lock-out relay to provide a manual reset at the thermostat in case of interrupted operation by the safety controls. The individual control components are designed for ease of inspection and serviceability. A terminal block is provided for convenient field wiring to the thermostat. A remote thermostat for comfort control is furnished with the unit.

SUPERIOR COOLING CAPACITIES AND PERFORMANCE

COOLING

In accordance with ARI Standard 240-67.

*Basis: 900 CFM of 80° F DB/67° F WB entering air

Cooling Capacity: 26,000 BTUH*.

3.65 GPM of Water entering at 75° F, leaving at 95° F.

Power Input: 3100 Watts.

APPLICATION DATA


ENTERING AIR (°F) WET BULB	BASED ON 900 CFM & 95°F LEAVING WATER					HEAT OF REJECTION (BTUH)
	TOTAL CAPACITY (BTUH)	SENSIBLE CAPACITY (BTUH) ENTERING AIR (°F) DRY BULB				
		75	80	85	90	
61	22600	17850	20100	—	—	32500
64	24500	16900	19600	22050	—	34700
67	26500	15900	18550	21200	23850	36500
70	28200	—	17200	19750	22850	38700
73	29900	—	—	18250	21250	41100

CORRECTION FACTORS

(A) VARIATION OF AIRFLOW

CFM	780	820	855	890	900	915	940	960
TOTAL CAPACITY	.946	.964	.980	.995	1.000	1.004	1.012	1.019
SENSIBLE CAPACITY	.930	.953	.973	.993	1.000	1.008	1.020	1.030
HEAT OF REJECTION	.958	.973	.985	.997	1.000	1.012	1.031	1.047

(B) VARIATION OF ENTERING WATER TEMP. AND FLOW RATE MULTIPLIER



TOTAL & SENSIBLE CAPACITY MULTIPLIER	HEAT OF REJECTION MULTIPLIER	POWER INPUT (WATTS)
0.930	0.960	3270
0.966	0.981	3180
1.000	1.000	3100
1.030	1.019	3020
1.057	1.041	2950

BLOWER PERFORMANCE (INCLUDES ALLOWANCE FOR WET COIL & FILTER)

SCFM @ AVAILABLE EXTERNAL STATIC PRESSURE (IWG)							
.10	.15	.20	.23	.25	.30	.35	.40
960	940	915	900	890	855	820	780

SAMPLE PROBLEM (COOLING)

915 CFM AIR ENTERING AT 75° DB/64° WB
5 GPM OF 75° F ENTERING WATER

AIRFLOW
CORRECTION

WATER FLOW
CORRECTION

TOTAL CAPACITY = 24500 X 1.004 X 1.030 = 25340 BTUH
SENSIBLE = 16900 X 1.008 X 1.030 = 17550 BTUH
HEAT REJECTION = 34700 X 1.012 X 1.019 = 35780 BTUH

SUPERIOR HEATING CAPACITIES AND PERFORMANCE


HEATING

In accordance with ARI Standard 240-67.
Heating Capacity: 26,000 BTUH*.
Power Input: 3100 Watts.

*Basis: 900 CFM of 70° F entering air
3.65 GPM of 60° F entering water.

APPLICATION DATA

VARIATION OF ENTERING WATER TEMPERATURE AND FLOW RATE



VARIATION OF ENTERING AIR TEMPERATURES CORRECTION FACTOR

ENTERING AIR (°F)	60	65	70	75	80
HEATING CAPACITY	1.05	1.03	1.00	.97	.94
HEAT OF ABSORPTION	1.07	1.04	1.00	.95	.94
POWER INPUT	.96	.98	1.00	1.04	1.08

VARIATION OF AIRFLOW CORRECTION FACTOR

CFM	780	820	855	890	900	915	940	960
HEATING CAPACITY	.946	.964	.980	.995	1.000	1.004	1.013	1.019
HEAT OF ABSORPTION	.936	.957	.976	.994	1.000	1.006	1.017	1.026
POWER INPUT	1.078	1.054	1.030	1.006	1.000	.996	.989	.983

WATER PRESSURE DROP-PSIG.

WATER FLOW RATE (GPM)	3	4	5	6	7	8
PRESSURE DROP (PSIG)	2.1	3.3	4.5	6.8	8.3	9.9

SAMPLE PROBLEM (HEATING)

915 CFM OF AIR ENTERING @70° F
5 GPM OF 67.5° F ENTERING WATER

ENTERING AIR
CORRECTION

AIRFLOW
CORRECTION


HEATING CAPACITY = 30700 X 1.00 X 1.004 = 30820 BTUH
HEAT OF ABSORPTION = 18800 X 1.00 X 1.006 = 18910 BTUH
POWER INPUT (WATTS) = 3350 X 1.00 X .996 = 3337 WATTS

Seasons Comfort At Less Cost


CHOOSE FROM VERTICAL AND HORIZONTAL STYLES

DIMENSIONAL DATA

VERTICAL MODEL



HORIZONTAL MODEL



CLIMATE MASTER FOR QUALITY AND ECONOMY

PHYSICAL DATA

SPECIFICATION CHART FOR VERTICAL AND HORIZONTAL MODELS

MODEL		V27-12	H27-12	V27-13	H27-13
CONFIGURATION		VERTICAL	HORIZONTAL	VERTICAL	HORIZONTAL
VOLTAGE *		208/230	208/230	277	277
PHASE		1	1	1	1
MIN. CIRCUIT AMPACITY		18.7	18.7	14.6	14.6
MAX. FUSE SIZE **		30	30	25	25
COMPRESSOR F.L.A.		13.0	13.0	10.8	10.8
COMPRESSOR L.R.A.		71	71	62	62
BLOWER F.L.A.		2.4	2.4	1.1	1.1
BLOWER MOTOR-HP		1/6	1/6	1/6	1/6
BLOWER WHEEL DIA.		9-1/2	9-1/2	9-1/2	9-1/2
BLOWER WHEEL LEN.		7-1/4	7-1/4	7-1/4	7-1/4
REF. TO AIR HEAT EXCHANGER	ROWS	3	3	3	3
	FACE AREA	2.29	2.29	2.29	2.29
	FINS/INCH	14	14	14	14
WATER INLET (FPT)		3/4	3/4	3/4	3/4
WATER OUTLET (FPT)		3/4	3/4	3/4	3/4
DRAIN (FPT)		3/4	3/4	3/4	3/4
FILTER SIZE		20 x 20	20 x 20	20 x 20	20 x 20
OPERATING, WT. (APPROX.)		260	270	260	270

* MIN. VOLTAGE ON 208/230 VOLT MODELS IS 197 VOLTS.

** TIME DELAY TYPE

NOTE: ALL UNITS ARE OPTIONALLY AVAILABLE WITH
CONTROLS FOR AN AUTOMATIC CHANGEOVER THERMOSTAT.

0274



CLIMATE MASTER PRODUCTS

DIVISION OF WEIL - MC LAIN COMPANY, INC.

2000 WEST COMMERCIAL BLVD., FORT LAUDERDALE, FLORIDA 33309 / 776-1961

In line with its policy of product improvement, Climate Master reserves the right to make reasonable changes without notice.

