




R-454B RESIDENTIAL

ALL PRODUCTS GUIDE



PACKAGED UNITS



TRANQUILITY® 30 (SE) PREMIER TWO-STAGE SERIES

- Sizes 024 (2 ton, 7 kW) through 072 (6 tons, 21.1 kW)
- Refrigerant Detection System (RDS) (mandatory on sizes 060 and 072, optional for sizes 024-048)
- iGate® 2 Advanced Communicating Controls for reduced startup, commissioning, and service time
- vFlow® unit integrated modulating water valve or variable speed pump
- Intelligent variable speed Constant Volume (CV) EC blower motors for precise airflow control and soft-start feature
- Unique double-isolation compressor mounting with vibration isolation for quiet operation
- Factory-installed compressor soft-starter
- Features a matte black polyester powder-coat finish cabinet with stainless steel access panels
- Two-Stage compressors offer part-load operation which significantly lowers annual operating costs when compared to traditional Single-Stage compressor systems



TRANQUILITY® 24 (SZ) VERSATILE TWO-STAGE SERIES

- Sizes 024 (2 ton, 7 kW) through 060 (5 tons, 17.6 kW)
- Refrigerant Detection System (RDS) (mandatory on sizes 060, optional feature for sizes 024-048)
- iGate® 2 Advanced Communicating Controls for reduced startup, commissioning, and service time
- vFlow® unit integrated modulating water valve or variable speed pump
- Intelligent variable speed Constant Volume (CV) EC blower motors for precise airflow control and soft-start feature
- Unique double-isolation compressor mounting with vibration isolation for quiet operation
- Factory-installed compressor soft-starter
- Features a matte black polyester powder-coat finish cabinet
- Two-Stage compressors offer part-load operation which significantly lowers annual operating costs when compared to traditional Single-Stage compressor systems

Tranquility® Low GWP Packaged Systems Comparison

● – Standard ○ – Optional

		Tranquility SE	Tranquility SZ
Efficiency	Cooling	29.7 EER	24.9 EER
	Heating	5.0 COP	4.2 COP
ENERGY STAR® Designation		Most Efficient	Most Efficient
Compressor		Two-Stage	Two-Stage
Communicating System		iGate® 2 DXM2.5 Unit Controls	
Advanced Monitoring and Diagnostics		●	●
Wi-Fi Communicating Thermostat		○	○
Hot Water Generation		○	○
		Supplemental	Supplemental
Front Panels		Stainless Steel	Powder Coated
Air Filter		2" MERV 11	1" MERV 8
vFlow® Internal Variable Water Flow		○	○
Indoor Fan	Variable Speed	●	●
	Vertical Upflow	○	○
	Horizontal	○	○
	Vertical Downflow	○	
Air Coil		Tin-Plated*	Tin-Plated
Swing Out Control Box		●	●
Warranty: 10-Year Parts; 5-Year Labor Allowance		●	●
Warranty: 10-Year Parts; 10-Year Labor Allowance		○	○

NOTES:

* SE024-048 uses Aluminum Micro-channel coil

R-454B Accessory Compatibility

Accessories	Packaged				Split		Water-to-Water	
	SE		SZ		SJ	SP	SA	SW
	Vertical	Horizontal	Vertical	Horizontal				
iGate® 2 Communicating (AWC) Thermostat	●	●	●	●	●	●	●	●
iGate® 2 Smart Tank	●	●	●	●	●			●
Wireless Service Tool	●	●	●	●	●	●	●	●
Secondary Drain Pan		●						
Tranquility Unit Vibration Isolation Pad	●		●		●			
Tranquility Unit Stand	●		●		●			
Auxiliary Electric Heater	●	●	●	●			●	
Outdoor Temperature Sensor	●	●	●	●	●	●		
Anti Scald Valve	●	●	●	●	●			●
Compressor Soft Start Kit	●	●	●	●	●	●		●

SPLIT SYSTEMS



TRANQUILITY® 30 (SJ) PREMIER INDOOR SPLIT SERIES

- Sizes 024 (2 ton, 7 kW) through 060 (5 tons, 21.1 kW)
- Environmentally friendly R-454B low-GWP refrigerant
- Refrigerant Detection System (RDS) factory installed
- Features a matte black polyester powder-coat finish with stainless steel access panels
- iGate® 2 Advanced Communicating Controls for reduced startup, commissioning, and service time
- vFlow® unit integrated modulating water valve or variable speed pump
- Two-Stage compressors offer part-load operation which significantly lowers annual operating costs when compared to traditional Single-Stage compressor systems



TRANQUILITY® 30 (SP) PREMIER OUTDOOR SPLIT SERIES

- Sizes 024 (2 ton, 7 kW) through 060 (5 tons, 21.1 kW)
- Environmentally friendly R-454B low-GWP refrigerant
- Features a bonded silver polyester powder coat finish
- iGate® 2 Advanced Communicating Controls for reduced startup, commissioning, and service time
- vFlow® unit integrated variable speed pump
- Two-Stage compressors offer part-load operation which significantly lowers annual operating costs when compared to traditional Single-Stage compressor systems



TRANQUILITY® (SA) PREMIER AIR HANDLER SERIES

- Sizes 024 (2 ton, 7kW) through 060 (5tons, 21.1kW)
- Environmentally friendly R-454B low-GWP refrigerant
- Refrigerant Detection System (RDS) factory installed on all sizes
- Intelligent variable speed Constant Volume (CV) EC blower motors for precise airflow control and soft-start feature
- Features a matte black polyester powder coat finish cabinet

SPLIT SYSTEMS



TRANQUILITY® (SK) PREMIER CASED COIL SERIES

- Sizes 024 (2 ton, 7 kW) through 060 (5 tons, 21.1 kW)
- Environmentally friendly R-454B low-GWP refrigerant
- Refrigerant Detection System (RDS) factory installed

WATER-TO-WATER UNITS



TRANQUILITY® (SW) WATER-TO-WATER SERIES

- Sizes 036 (3 ton, 10.6 kW) through 120 (10 tons, 35.2 kW)
- Environmentally friendly R-454B low-GWP refrigerant
- vFlow® modulating water valves
- vFlow® Source and Load side variable speed water pumps
- Features a matte black polyester powder coat finish cabinet
- iGate® 2 Advanced Communicating Controls for reduced startup, commissioning, and service time
- Two-Stage compressors offer part-load operation which significantly lowers annual operating costs when compared to traditional Single-Stage compressor systems

ALL PRODUCTS EXCEED ASHRAE 90.1 EFFICIENCY REQUIREMENTS



7300 SW 44th St | Oklahoma City, OK 73179
Phone: 405.745.6000
www.climatemaster.com



ClimateMaster works continually to improve its products. As a result, the design and specifications of each product at the time of order may be changed without notice and may not be as described herein. Please contact ClimateMaster's Customer Service Department at 405-745-6000 for specific information on the current design and specifications. Statements and other information contained herein are not express warranties and do not form the basis of any bargain between the parties, but are merely ClimateMaster's opinion or commendation of its products. The latest version of this document is available at www.climatemaster.com.
Engineered and assembled in the USA. © ClimateMaster, Inc. All Rights Reserved 2025