



Tranquility[®] 22 Compact (TY) Series

Models TYH/V024 -060 60Hz - HFC 410A

The Tranquility[®] Compact (TY) Series offers high efficient two-stage operation in a simple cabinet design. With one of the smallest cabinets in the industry, the Tranquility[®] 22 Compact (TY) Series will easily fit into tight spaces. Designed to be backward compatible with thousands of older water-source heat pumps.

Advantages of the Compact TY Series:

- Advanced Controls - iGate[®] communicating control provides advanced unit functionality and comprehensive configuration, monitoring and diagnostic capabilities through digital communication links with the variable-speed fan motor, and communicating thermostat or configuration/diagnostic tool
- Galvanized steel drain pan with powder coat finish
- Sound absorbing glass fiber insulation
- Unique double isolation compressor mounting for quiet operation
- Insulated divider and separate compressor/air handler compartments
- Field convertible discharge air arrangement for horizontal units
- Variable speed ECM fan motor
- Internally trapped condensate drain line (vertical units only)
- Eight safeties standard
- Extended range (20 to 120°F, -6.7 to 48.9°C) capable

Unit Size

Vertical Upflow Model		A Width	B Depth	C Height
024 - 030	in.	21.5	21.5	40.0
	cm	54.6	54.6	101.6
036 - 042	in.	21.5	26.0	45.0
	cm	54.6	66.0	114.3
048 - 060	in.	24.0	32.5	46.0
	cm	61.0	82.6	116.8

Horizontal Model		A Width	B Length	C Height
024 - 030	in.	20.1	43.1	18.3
	cm	51.1	109.5	46.5
036 - 042	in.	20.1	47.1	21.0
	cm	51.1	119.6	53.3
048 - 060	in.	24.1	54.1	21.0
	cm	61.2	137.4	53.3

Physical Data

Model	024	030	036	042	048	060
Compressor (1 Each)	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
Factory Charge HFC-410A (oz) [kg]	51	48	54	70	80	80
ECM Fan Motor & Blower						
Fan Motor (hp) [W]	1/2	1/2	1/2	3/4	3/4	1
Blower Wheel Size (dia x w) - (in) [mm]	9X7	9X7	9X8	9X8	10X10	11X10
Water Connection Size						
FPT (in)	3/4"	3/4"	3/4"	3/4"	1"	1"
Coax Volume (gallons)	0.323	0.323	0.738	0.89	0.738	0.939
Vertical Upflow						
Air Coil Dimensions (h x w) - (in) [mm]	20 X 17.25	20 X 17.25	24 X 21.75	24 X 21.75	24x28.25	24x28.25
Standard Filter - 1" [25.4mm] Throwaway, qty (in) [mm]	20x20	20x20	24x24	24x24	1-14x24 1-18x24	1-14x24 1-18x24
Weight - Operating, (lbs) [kg]	189	197	203	218	263	278
Weight - Packaged, (lbs) [kg]	194	202	209	224	270	285
Horizontal						
Air Coil Dimensions (h x w) - (in) [mm]	16 X 22	16 X 22	20 X 25	20 X 25	20 X 35	20 X 35
Standard Filter - 1" [25.4mm] Throwaway, qty (in) [mm]	18x25	18x25	2-14x20	2-14x20	1-20x24 1-14x20	1-20x24 1-14x20
Weight - Operating, (lbs) [kg]	174	182	203	218	263	278
Weight - Packaged, (lbs) [kg]	179	187	209	224	270	285

Notes:

All units have TXV expansion device and 1/2" & 3/4" electrical knockouts.

Tested To ASHRAE/AHRI/ISO 13256-1 English Units

Model	Water Loop Heat Pump				Ground Water Heat Pump				Ground Loop Heat Pump			
	Cooling 86°F		Heating 68°F		Cooling 59°F		Heating 50°F		Full Cool 77°F Part Cool 68°F		Full Heat 32°F Part Heat 41°F	
	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP
TY*024 Part	18,100	16.1	20,600	5.2	20,300	27.2	16,700	4.4	19,400	22.2	14,700	4.0
TY*024 Full	23,700	14.3	28,000	4.6	26,500	21.7	23,000	4.1	24,600	16.0	17,800	3.6
TY*030 Part	21,900	15.2	26,300	5.0	24,900	24.8	22,000	4.3	24,200	20.9	19,400	3.9
TY*030 Full	28,500	14.0	35,800	4.6	32,300	20.7	30,000	4.2	29,900	15.7	23,800	3.6
TY*036 Part	25,800	17.2	29,900	5.3	29,000	29.4	24,900	4.6	27,300	23.4	21,500	4.0
TY*036 Full	34,300	15.1	42,000	4.6	38,200	22.3	35,100	4.3	35,200	16.7	27,300	3.6
TY*042 Part	31,000	15.8	36,800	5.1	35,200	26.4	30,500	4.3	34,000	22.0	26,900	3.8
TY*042 Full	41,100	14.3	50,200	4.6	46,300	21.3	42,300	4.1	43,100	16.1	33,300	3.4
TY*048 Part	34,100	15.2	39,500	5.5	39,200	26.8	32,600	4.6	37,600	21.2	29,200	4.1
TY*048 Full	45,900	14.0	53,800	4.9	51,800	20.9	45,000	4.4	48,100	15.5	35,600	3.7
TY*060 Part	45,500	17.7	49,000	5.3	50,400	28.9	39,800	4.5	48,600	23.7	34,800	4.0
TY*060 Full	61,700	15.7	67,500	4.8	68,000	22.7	55,400	4.3	63,200	17.3	43,700	3.6

Cooling capacities based upon 80.6°F DB, 66.2°F WB entering air temperature

Heating capacities based upon 68°F DB, 59°F WB entering air temperature

Ground Loop Heat Pump ratings based on 15% antifreeze solution

All ratings based upon operation at lower voltage of dual voltage rated models

All rating based upon operation at lower voltage of dual voltage rated models

* Includes vertical and horizontal configurations



7300 S.W. 44th Street
Oklahoma City, OK 73179
Phone: 405-745-6000
climatemaster.com

